



圆柱型电感式接近开关(DC 3线式)

M5, $\Phi 6.5$

[illegible]

M5x38			Φ6.5x16		
0.8mm		1.5mm	1.5mm		2.0mm
埋入		埋入	埋入		埋入
IM5-M0.8NA-Y3V3/S38	1	IZM5-M1.5NA-Y3V3/S38	IO6.5-M1.5NA-Y3L2/S16	1	IZO6.5-M02NA-Y3L2/S16
IM5-M0.8NB-Y3V3/S38	2	IZM5-M1.5NB-Y3V3/S38	IO6.5-M1.5NB-Y3L2/S16	2	IZO6.5-M02NB-Y3L2/S16
IM5-M0.8PA-Y3V3/S38	4	IZM5-M1.5PA-Y3V3/S38	IO6.5-M1.5PA-Y3L2/S16	4	IZO6.5-M02PA-Y3L2/S16
IM5-M0.8PB-Y3V3/S38	5	IZM5-M1.5PB-Y3V3/S38	IO6.5-M1.5PB-Y3L2/S16	5	IZO6.5-M02PB-Y3L2/S16
					
					
0.8mm±10%		1.5mm±10%	1.5mm±10%		2.0mm±10%
1~10%		1~10%	1~10%		1~10%
铁5x5x1mm		铁5x5x1mm	铁8x8x1mm		铁8x8x1mm
3000Hz		2500Hz	2500Hz		2000Hz
≤Sn±3%			≤Sn±3%		
≤0.01mA			≤0.01mA		
≤10mA			≤15mA		
≤200mA			≤200mA		
≤2V			≤2V		
极性反接保护;上电脉冲抑制保护;负载短路保护			极性反接保护;负载短路保护		
动作指示灯(黄色)			动作指示灯(黄色)		
-25~+70℃			-25~+70℃		
≤Sn±10%			≤Sn±10%		
-25~+80℃			-25~+80℃		
50MΩ以上(DC 500V兆欧表),充电部整数和外壳之间			50MΩ以上(DC 500V兆欧表),充电部整数和外壳之间		
符合标准EN60947-5-2			符合标准EN60947-5-2		
IP67			IP67		
3针M8连接器			电缆线2M; 外径 Φ3.2mm		
外壳材料:不锈钢;检测面材料:塑料			外壳材料:不锈钢;检测面材料:塑料		
注: 1,2,4,5为接线图号, 请见05页。 * : 为全功能输出型, 详见169页说明					