




圆柱型电感式接近开关(DC 3线式)

Φ 6.5

[illegible]

Φ6.5x34				Φ6.5x30			
1.5mm		2.0mm		1.5mm		2.5mm	
埋入		埋入		埋入		非埋	
IO6.5-M1.5NA-Y3V3/S34	1	IZO6.5-M02NA-Y3V3/S34		IO6.5-M1.5NA-Y3L2/S30	1	IO6.5-F2.5NA-Y3L2/S30	
IO6.5-M1.5NB-Y3V3/S34	2	IZO6.5-M02NB-Y3V3/S34		IO6.5-M1.5NB-Y3L2/S30	2	IO6.5-F2.5NB-Y3L2/S30	
IO6.5-M1.5PA-Y3V3/S34	4	IZO6.5-M02PA-Y3V3/S34		IO6.5-M1.5PA-Y3L2/S30	4	IO6.5-F2.5PA-Y3L2/S30	
IO6.5-M1.5PB-Y3V3/S34	5	IZO6.5-M02PB-Y3V3/S34		IO6.5-M1.5PB-Y3L2/S30	5	IO6.5-F2.5PB-Y3L2/S30	
				 			
				 			
1.5mm±10%		2.0mm±10%		1.5mm±10%		2.5mm±10%	
1~10%		1~10%		1~10%		1~10%	
铁8x8x1mm		铁8x8x1mm		铁8x8x1mm		铁8x8x1mm	
2500Hz		2000Hz		2500Hz		2000Hz	
≤Sn±3%				≤Sn±3%			
≤0.01mA				≤0.01mA			
≤10mA				≤10mA			
≤200mA				≤200mA			
≤2V				≤2V			
极性反接保护;负载短路保护				极性反接保护;上电脉冲抑制保护;负载短路保护			
动作指示灯(黄色)				动作指示灯(黄色)			
-25~+70℃				-25~+70℃			
≤Sn±10%				≤Sn±10%			
-25~+80℃				-25~+80℃			
50MΩ以上(DC 500V兆欧表),充电部整数和外壳之间				50MΩ以上(DC 500V兆欧表),充电部整数和外壳之间			
符合标准EN60947-5-2				符合标准EN60947-5-2			
IP67				IP67			
3针M8连接器				电缆线2M; 外径 Φ3.2mm			
外壳材料:不锈钢;检测面材料:塑料				外壳材料:不锈钢;检测面材料:塑料			
注: 1,2,4,5为接线图号, 请见05页。 *: 为全功能输出型, 详见169页说明							