

圆柱型电感式接近开关(DC 3线式)

Φ 6.5

[illegible]

Φ6.5x45			Φ6.5x50		
3.0mm		6.0mm	1.5mm		2.5mm
埋入		非埋	埋入		非埋
ILO6.5-M03NA-Y3V3/C45	1	ILO6.5-F06NA-Y3V3/C45	IO6.5-M1.5NA-Y3U4/S50	1	IO6.5-F2.5NA-Y3U4/S50
ILO6.5-M03NB-Y3V3/C45	2	ILO6.5-F06NB-Y3V3/C45	IO6.5-M1.5NB-Y3U4/S50	2	IO6.5-F2.5NB-Y3U4/S50
ILO6.5-M03PA-Y3V3/C45	4	ILO6.5-F06PA-Y3V3/C45	IO6.5-M1.5PA-Y3U4/S50	4	IO6.5-F2.5PA-Y3U4/S50
ILO6.5-M03PB-Y3V3/C45	5	ILO6.5-F06PB-Y3V3/C45	IO6.5-M1.5PB-Y3U4/S50	5	IO6.5-F2.5PB-Y3U4/S50
3.0mm±10%		6.0mm±10%	1.5mm±10%		2.5mm±10%
1~10%		1~10%	1~10%		1~10%
铁9x9x1mm		铁18x18x1mm	铁8x8x1mm		铁8x8x1mm
1000Hz		500Hz	2500Hz		2000Hz
≤Sn±3%			≤Sn±3%		
≤0.01mA			≤0.01mA		
≤10mA			≤10mA		
≤200mA			≤200mA		
≤2V			≤2V		
极性反接保护;上电脉冲抑制保护;负载短路保护			极性反接保护;上电脉冲抑制保护;负载短路保护		
动作指示灯(黄色)			动作指示灯(黄色)		
-25~+70℃			-25~+70℃		
≤Sn±10%			≤Sn±10%		
-25~+80℃			-25~+80℃		
50MΩ以上(DC 500V兆欧表);充电部整数和外壳之间			50MΩ以上(DC 500V兆欧表);充电部整数和外壳之间		
符合标准EN60947-5-2			符合标准EN60947-5-2		
IP67			IP67		
3针M8连接器			4针M12连接器		
外壳材料:黄铜镀镍;检测面材料:塑料			外壳材料:不锈钢;检测面材料:塑料		
注: 1,2,4,5为接线图号, 请见05页。 * : 为全功能输出型, 详见169页说明					