

M12x50		M12x60				M12x60					
4mm		8mm		2mm		4mm		4mm		8mm	
埋入		非埋		埋入		非埋		埋入		非埋	
IMM12-M04V1-Y3L2/C50	17	IMM12-F08V1-Y3L2/C50		IMM12-M02V1-Y3U4/C60	17	IMM12-F04V1-Y3U4/C60		IMM12-M04V1-Y3U4/C60	17	IMM12-F08V1-Y3U4/C60	
IMM12-M04I1-Y3L2/C50	18	IMM12-F08I1-Y3L2/C50		IMM12-M02I1-Y3U4/C60	18	IMM12-F04I1-Y3U4/C60		IMM12-M04I1-Y3U4/C60	18	IMM12-F08I1-Y3U4/C60	
IMM12-M04M1-Y3L2/C50	19	IMM12-F08M1-Y3L2/C50		IMM12-M02M1-Y3U4/C60	19	IMM12-F04M1-Y3U4/C60		IMM12-M04M1-Y3U4/C60	19	IMM12-F08M1-Y3U4/C60	
IMM12-M04V2-Y4L2/C50	17	IMM12-F08V2-Y4L2/C50		IMM12-M02V2-Y4U4/C60	17	IMM12-F04V2-Y4U4/C60		IMM12-M04V2-Y4U4/C60	17	IMM12-F08V2-Y4U4/C60	
IMM12-M04I2-Y4L2/C50	18	IMM12-F08I2-Y4L2/C50		IMM12-M02I2-Y4U4/C60	18	IMM12-F04I2-Y4U4/C60		IMM12-M04I2-Y4U4/C60	18	IMM12-F08I2-Y4U4/C60	
IMM12-M04M2-Y4L2/C50	19	IMM12-F08M2-Y4L2/C50		IMM12-M02M2-Y4U4/C60	19	IMM12-F04M2-Y4U4/C60		IMM12-M04M2-Y4U4/C60	19	IMM12-F08M2-Y4U4/C60	
1~4mm	2~8mm	0.3~2mm	1~4mm	1~4mm	4~8mm						
---	---	---	---	---	---						
铁12x12x1mm	铁24x24x1mm	铁12x12x1mm	铁12x12x1mm	铁12x12x1mm	铁12x12x1mm	铁12x12x1mm	铁24x24x1mm				
100Hz	80Hz	200Hz	100Hz	100Hz	80Hz						
≤Sn±1%		≤Sn±1%				≤Sn±1%					
电压 ≥500Ω / 电流 ≤500Ω		电压 ≥500Ω / 电流 ≤500Ω				电压 ≥500Ω / 电流 ≤500Ω					
≤15mA		≤15mA				≤15mA					
0~5VDC / 0~10VDC		0~5VDC / 0~10VDC				0~5VDC / 0~10VDC					
1~5mA / 4~20mA		1~5mA / 4~20mA				1~5mA / 4~20mA					
极性反接保护,短路保护		极性反接保护,短路保护				极性反接保护,短路保护					
无		无				无					
-25~+70°C		-25~+70°C				-25~+70°C					
≤Sn±10%		≤Sn±10%				≤Sn±10%					
-25~+80°C		-25~+80°C				-25~+80°C					
50MΩ以上(DC 500V兆欧表), 充电部整数和外壳之间		50MΩ以上(DC 500V兆欧表), 充电部整数和外壳之间				50MΩ以上(DC 500V兆欧表), 充电部整数和外壳之间					
符合标准EN60947-5-2		符合标准EN60947-5-2				符合标准EN60947-5-2					
IP67		IP67				IP67					
电缆线2M; 外径 φ4.0mm		4针M12连接器				4针M12连接器					
外壳材料:黄铜镀镍;检测面材料:塑料		外壳材料:黄铜镀镍;检测面材料:塑料				外壳材料:黄铜镀镍;检测面材料:塑料					

注: 17,18,19为接线图号, 请见05页。

1 电感式传感器

2 电容式传感器

3 磁感式传感器

4 光电传感器

5 传感器附件

6 词汇表